

Regenerating paint on bitumen base, solvent-containing, filled roof coating for refurbishing bitumen roof surfaces.

Characteristics

DAKORIT® RA 30B is a viscous, filled bitumen roof paint.

Additives in the paint penetrate into the upper zones of the old roof covering and have a regenerative action. High UV and weathering resistance as compared to the traditional bitumen paints thanks to the selected filler combinations.

Good corrosion protection on metal because of the high coat thicknesses with one-off paint.

- Solvent-containing
- Viscous
- Highly adhesive
- High plasticity range
- UV and weathering resistant

Use

DAKORIT® RA 30B for refurbishing and renovation of bitumen roof sealing.

As protective coating on metal.

Area of application:

- Old roof surfaces and roof sealing

Specifications

Packaging	Tin bucket
Barrel	25 kg
Delivery form	16 barrels/pallet
Drying ¹⁾	approx. 3 hours
Storage	18 months

Quantity required

Per application	0.5 - 0.7 kg/m ²
-----------------	-----------------------------

¹⁾ At +20 °C and 60 % relative atmospheric humidity.

Preparation of the surface

Clean the roof surfaces and prime them with a solvent-containing primer (**DAKORIT® VA 30B**). Close cracks with **DAKORIT® SPM 40B**.

Application

1. The **DAKORIT® RA 30B** coat is applied with the roofers' brush approx. 3 hours after the primer.
2. Clean all the processing equipment after use with **HADALAN® EPV 38L**.

hahne system products

DAKORIT® VA 30B
DAKORIT® SPM 40B
HADALAN® EPV 38L

Important notes

- Use outdoors only.
- Contains flammable solvent.

Ingredients

Bitumen, adhesive agent, organic solvents, functional filters, fibres

Safety provisions/recommendations

Information regarding the safety during transport, storage and handling are included in the updated safety data sheet.

Disposal

The local waste removal regulations must be observed.

Manufacturer

Heinrich Hahne GmbH & Co KG
Heinrich-Hahne-Weg 11
D-45711 Datteln

This information is based on extensive tests and practical experience. However, it cannot be applied to every type of application. If in doubt, we recommend that you test the product before using it. Due to continuous product improvement, this information is subject to change without notice. Our General Terms and Conditions apply. Version as of 2.2016